

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A method for operating a lithium ion secondary battery system comprising:

carrying out an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is discharged with not less than a predetermined discharge rate, and

wherein said pause is executed for a period not less than the period required for the voltage of the lithium ion secondary battery to restore up to not less than 70% of an open circuit voltage.

2. (currently amended): The method for operating the lithium ion secondary battery system as set forth in claim 1, wherein said pause is executed ~~for a period not less than the period required for the voltage of the lithium ion secondary battery to restore up to not less than 70% of the open circuit voltage~~ after the lithium ion secondary battery is discharged until the voltage thereof reaches the discharge end voltage, when the lithium ion secondary battery is discharged.

3. (previously presented): The method for operating the lithium ion secondary battery system as set forth in claim 1, wherein an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is charged with not less than a predetermined charge rate, wherein said pause is executed for a period not less than the period required for the voltage of the lithium ion secondary battery to go down by not less than 70% of a voltage difference between the open circuit voltage and the charge end

voltage after the lithium secondary battery is charged until the voltage thereof reaches the charge end voltage, when the lithium ion secondary battery is charged.

4. (previously presented): The method for operating the lithium ion secondary battery

system as set forth in claim 1, wherein said intermittent power feeding is carried out when the discharge rate is not less than 5C.

5. (previously presented): The method for operating the lithium ion secondary battery system as set forth in claim 1, wherein the lithium ion secondary battery includes a positive active material having an average discharge potential to the lithium metal of not less than 4.5V.

6. (previously presented): The method for operating the lithium ion secondary battery system as set forth in claim 1, wherein the lithium ion secondary battery is incorporated in a power supply device of an electric automobile or a hybrid automobile.

7. (currently amended): A lithium ion secondary battery system comprising:
a lithium ion secondary battery; and
a control unit which carries out an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is discharged with not less than a predetermined discharge rate, and
wherein said control unit executes said pause for a period not less than the period required for the voltage of the lithium ion secondary battery to restore up to not less than 70% of an open circuit voltage.

8. (currently amended): The lithium ion secondary battery system as set forth in claim 7, wherein said control unit executes said pause ~~for a period not less than the period required for the voltage of the lithium ion secondary battery to restore up to not less than 70% of the open circuit voltage~~ after the lithium ion secondary battery is discharged until the voltage thereof reaches the discharge end voltage, when the lithium ion secondary battery is discharged.

9. (previously presented): The lithium ion secondary battery system as set forth in claim 7, further comprising a voltage measuring unit which measures a voltage of the lithium ion secondary battery, wherein an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is charged with not less than a predetermined charge rate, wherein said control unit executes said pause for a period not less than the period required for the voltage of the lithium ion secondary battery go down by not less than 70% of a voltage difference between the open circuit voltage and the charge end voltage after the lithium secondary battery is charged until the voltage thereof reaches the charge end voltage, when the lithium ion secondary battery is charged.

10. (previously presented): The lithium ion secondary battery system as set forth in claim 7, further comprising a detection unit which detects the discharge rate of the lithium ion secondary battery, wherein said control unit carries out said intermittent power feeding when the discharge rate of the lithium ion secondary battery is not less than 5C.

11. (previously presented): The lithium ion secondary battery system as set forth in claim 7, wherein the lithium ion secondary battery includes a positive active material having an average discharge potential to the lithium metal of not less than 4.5V.

12. (previously presented): The lithium ion secondary battery as set forth in claim 7, wherein the lithium ion secondary battery is incorporated in a power supply device of an electric automobile or a hybrid automobile.

13. (previously presented): The method for operating the lithium ion secondary battery as set forth in claim 1, wherein an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is charged with not less than a predetermined charge rate.

14. (previously presented): The method for operating the lithium ion secondary battery as set forth in claim 13, wherein said intermittent power feeding is carried out when the charge rate is not less than 5C.

15. (previously presented): The lithium ion secondary battery system as set forth in claim 7, further comprising a detection unit which detects the charge rate of the lithium ion secondary battery, wherein said control unit carries out an intermittent power feeding in which a power feeding and a pause are repeatedly executed, when a lithium ion secondary battery is charged with not less than a predetermined charge rate.

16. (previously presented): The lithium ion secondary battery system as set forth in claim 15, further comprising a detection unit which detects the charge rate of the lithium ion secondary battery, wherein said control unit carries out said intermittent power feeding when the charge rate of the lithium ion secondary battery is not less than 5C.